






COMPACT 50L SMART THINGS COME IN SMALL PACKAGES

Designed to be everything you asked for in a compact water heater, the 50 Litre Electric is MEPS compliant.

We solved the access problem by relocating all the service outlets to the front and unlike some units, ours have remained smaller in size.







160L SQUAT A BIG TANK MADE FOR SHORT SPACES

The AquaMAX commitment to innovation continues with the 160 Litre Electric Squat. An Electric Water Heater that brings larger capacity to awkward indoor spaces. With dual inlets and outlets, the 160 Litre Electric Squat brings reliable delivery in a smarter package.



250L-400L ELECTRICS BIG DELIVERY, LOWER RUNNING COSTS

The AquaMAX large Electric water heater range provides an option to take advantage of lower cost off-peak tariffs.² Built with dual inlets and outlets (like the rest of the range), the 250-400 Litre Electric range is available in single or twin element models.


Water Heater Dimensions (mm)	Н	A	В	D
991050	695	539	142	400
981080	875	669	194	460
991125	1340	1166	64	480
991160	1610	1436	104	480
9W1160	965	755	113	640
991250/992250	1395	1190	73	640
991315/992315	1640	1430	113	640
991400/992400	1840	1600	121	690

Aquamax Australia Pty Ltd 463-467 Warrigal Road Moorabbin Vic 3189 **Toll Free: 1800 676 000** Ph: (03) 9532 2200 Sales Fax: 1800 639 844 Service Fax: (03) 9556 5534 AB.N. 37 138 189 689 Email: sales@aquamax.com.au For more information visit **www.aquamax.com.au**













Stay in hot water with AquaMAX.

Award winning AquaMAX high efficiency Electric Water Heaters provide your family with all the hot water they need.

AquaMAX Mains Pressure Electric Water Heaters are built using the latest technology and backed by a <u>7 or 5 year</u> cylinder warranty.¹ They are available in sizes to suit most applications.

AquaMAX Electric Water Heaters are made for Aussie conditions, to suit both metro and regional areas.

FAMILIES BIG AND SMALL

AquaMAX Electric Mains Pressure Water Heaters provide families big and small with reliable hot water. AquaMAX inhouse factory testing ensures every new system we build meets our exacting standards whether it's installed indoors or outdoors. You can also take advantage of lower cost off-peak tariffs for added savings on your energy bills.²

HOW DO WE MAKE THEM ACHIEVE OUR STANDARD?

After our cylinders have been fully welded, we apply a high quality enamel coating using the latest multi-head spray equipment to create our enamel lining. Combined with a sacrificial anode and protected by a steel casing with rounded edges, every AquaMAX Electric Water Heater is backed by a 7 or 5 year cylinder warranty.¹

		4	00 Litr	e		315	Litre		250 Litre 160 Litre Squat 160 Litre		125 Litre			80 Litre	50 Litre							
Electric Specifications		991400G7	991400G8	992400G8	991315G7	991315G8	992315G7	992315G8	991250G7	991250G7/BL	991250G8	992250G7	9W1160G4	9W1160G5	991160G4	991160G5	991160G7	991125G4	991125G4/BL	991125G7	981080G7	991050G7
Number of People Serviced - Continuous/Time of Use Tariff	f		5-9			4-	-6			3-	-5		2-	-4		2-4			2-3		1-2	1
- Off peak/night rate		4-6		2-4			1-3					-		-	-							
Hot Water Delivery	Litres	400		315			250			160		160		125			80	50				
Boost Capacity (Twin Element)	Litres	-	-	90	-	-	5	0		-		50	-	-		-			-		-	-
Weight (empty)	kg		118		97		76			63		55		49			32	29				
Maximum Loading	Watts	3600	4800	4800	3600	4800	3600	4800	3600	3600	4800	3600	1800	2400	1800	2400	3600	1800	1800	3600	3600	3600
Heating Element Upper	Watts	-	-	4800	-	-	3600	4800		-		3600 – – –		_				-				
Heating Element Lower	Watts	3600	4800	4800	3600	4800	3600	4800	3600	3600	4800	3600	1800	2400	1800	2400	3600	1800	1800	3600	3600	3600



Specifications	991400	991315	991250	9W1160	991160	991125	981080	991050		
Voltage (single phase)	240Vac	240Vac				240	Vac	240Vac		
Maximum Supply Pressure										
with expansion control valve (ECV)	680 kPa	(680 kPa	a	960	kPa	680 kPa	960 kPa		
without expansion control valve (ECV)	800 kPa	8	800 kPa	00 kPa) kPa	800 kPa	1120 kPa		
Pressure & Temp Relief Valve	1000 kPa	1000 kPa			1400 kPa		1000 kPa	1400 kPa		
ECV setting	850 kPa	850 kPa			1200 kPa		850 kPa	1200 kPa		
Thermostat setting (Maximum)	70°C		70°C			70°	,C	75°C		
Hot & Cold Water connection	Rp 3/4" (20mm) Female		Rp 3/4" (20mm) Female			/4" (20n	nm) Female	Rp 3/4" (20mm) Female		
Warranty (Cylinder) ¹	7 years*	7* or 5 years				5 ye	ars	5 years		
Warranty (Parts & Labour) ¹	1 year	1 year				1 ye	ear	1 year		
Protection rating	IP24	IP24			IP2	.4	IP24			

^{* 7} year cylinder warranty applies to 991400, 992400, 991315, 992315, 991250 & 992250 models manufactured on or after 1/10/2015.

Due to constant product improvements, the specifications are subject to change without notice.

^{1 7} year cylinder warranty applies to 250L, 315L and 400L models manufactured on or after 1/10/2015. Full warranty details available on request from AquaMAX. Call Toll Free 1800 676 000 or view at www.aquamax.com.au

² Please refer to your energy provider